

GraphQL - Input objects

ActivityCreateInput

Arguments

Name	Description
subject <code>ActivitySubject!</code>	
subjectId <code>Int!</code>	
category <code>ActivityCategory!</code>	
deadlineDate <code>Date</code>	
doneDate <code>Date</code>	
note <code>String</code>	
staffId <code>Int</code>	

ActivityFilters

Arguments

Name	Description
q <code>String</code>	
order <code>String</code>	
dueDate <code>DateRange</code>	
userId <code>Int</code>	
supporterId <code>Int</code>	

Name	Description
donationId Int	

ActivityUpdateInput

Arguments

Name	Description
category ActivityCategory	
deadlineDate Date	
doneDate Date	
note String	
staffId Int	

ArticleInput

Arguments

Name	Description
title String	
content String	
visibility WebDocumentVisibility	
slug String	
seoTitle String	
seoDescription String	
template String	
coverId Int	

Name	Description
blogId <code>Int</code>	

ArticlesFiltersInput

Arguments

Name	Description
q <code>String</code>	

BlogInput

Arguments

Name	Description
title <code>String</code>	
content <code>String</code>	
visibility <code>WebDocumentVisibility</code>	
slug <code>String</code>	
seoTitle <code>String</code>	
seoDescription <code>String</code>	
template <code>String</code>	
coverId <code>Int</code>	

BlogsFiltersInput

Arguments

Name	Description
------	-------------

q
String

CampaignCommentCreateInput

Arguments

Name	Description
donationId Int!	
message String!	
status CampaignCommentStatus!	
public Boolean!	
anonymous Boolean!	

CampaignCommentsFilters

Arguments

Name	Description
q String	
supporterId Int	
campaignId Int	
donationId Int	
status CampaignCommentStatus	

CampaignCommentUpdateInput

Arguments

Name	Description
------	-------------

message <code>String</code>	
status <code>CampaignCommentStatus</code>	
public <code>Boolean</code>	
anonymous <code>Boolean</code>	

CampaignFilters

Arguments

Name	Description
q <code>String</code>	
order <code>String</code>	
tags <code>[String!]</code>	
tagsNot <code>[String!]</code>	
channels <code>[String!]</code>	
ids <code>[Int!]</code>	
visibility <code>WebDocumentVisibility</code>	

CampaignInput

Arguments

Name	Description
title <code>String</code>	
content <code>String</code>	
visibility <code>WebDocumentVisibility</code>	

Name	Description
slug <code>String</code>	
seoTitle <code>String</code>	
seoDescription <code>String</code>	
template <code>String</code>	
thankyouTemplate <code>String</code>	
receiptNotificationId <code>Int</code>	
coverId <code>Int</code>	
isGoalEnabled <code>Boolean</code>	
code <code>String</code>	
goal <code>Float</code>	
type <code>CampaignType</code>	
tags <code>[String!]</code>	
excludedChannels <code>[Int!]</code>	
allowPeerToPeer <code>Boolean</code>	
costExamples <code>[CostExampleInput!]</code>	
hasOneOff <code>Boolean</code>	
hasSubscription <code>Boolean</code>	
hasSubscriptionCustomOptions <code>Boolean</code>	
defaultAmount <code>Float</code>	
minAmount <code>Float</code>	
maxAmount <code>Float</code>	

Name	Description
asks <code>[Float!]</code>	
allowCustomAmount <code>Boolean</code>	
defaultSubscriptionAmount <code>Float</code>	
minSubscriptionAmount <code>Float</code>	
maxSubscriptionAmount <code>Float</code>	
asksSubscription <code>[Float!]</code>	
allowCustomSubscriptionAmount <code>Boolean</code>	
shownFields <code>[String!]</code>	
requiredFields <code>[String!]</code>	
privacyFields <code>[String!]</code>	
privacyNote <code>String</code>	

CheckoutCompleteInput

Arguments

Name	Description
paymentMethodId <code>Int</code>	

CheckoutFilters

Arguments

Name	Description
q <code>String</code>	
state <code>CheckoutState</code>	

Name	Description
order <code>String</code>	
tags <code>[String!]</code>	
tagsNot <code>[String!]</code>	
createDate <code>DateRange</code>	
updateDate <code>DateRange</code>	
completedDate <code>DateRange</code>	

CheckoutInput

Arguments

Name	Description
campaignId <code>Int</code>	
supporterId <code>Int</code>	
costExampleQuantity <code>Int</code>	
peerCampaignId <code>Int</code>	
amount <code>Float</code>	
frequency <code>Frequency</code>	
isPromise <code>Boolean</code>	
tags <code>[String!]</code>	
paymentMethodId <code>Int</code>	
supporterData <code>SupporterInput</code>	
donationData <code>DonationInput</code>	

Name	Description
device <code>String</code>	
applicationId <code>Int</code>	
applicationMetadata <code>JSON</code>	

CheckoutPaymentInput

Arguments

Name	Description
state <code>PaymentState</code>	
amount <code>Float</code>	
paymentDate <code>DateTime</code>	
donationId <code>Int</code>	
paymentMethodId <code>Int</code>	
peerCampaignId <code>Int</code>	
creditCardId <code>Int</code>	
sepaBankAccountId <code>Int</code>	
stripePaymentIntentId <code>String</code>	
satisfyPaymentIntentId <code>String</code>	

CostExampleInput

Arguments

Name	Description
uuid <code>String!</code>	

Name	Description
name <code>String!</code>	
description <code>String!</code>	
amount <code>Float!</code>	
imageId <code>Int</code>	
monitorQuantity <code>Boolean!</code>	
quantity <code>Int!</code>	
availableQuantity <code>Int!</code>	

CustomFieldDefinitionCreateInput

Arguments

Name	Description
entity <code>CustomFieldEntity!</code>	
name <code>String!</code>	
description <code>String</code>	
type <code>CustomFieldType!</code>	
position <code>Int</code>	
options <code>[String!]</code>	

CustomFieldDefinitionUpdateInput

Arguments

Name	Description
name <code>String</code>	

Name	Description
description <code>String</code>	
position <code>Int</code>	
options <code>[String!]</code>	
archived <code>Boolean</code>	

CustomFieldEntityFilter

Arguments

Name	Description
key <code>String!</code>	
value <code>String</code>	
defined <code>Boolean</code>	

CustomFieldFilters

Arguments

Name	Description
entity <code>CustomFieldEntity</code>	
archived <code>Boolean</code>	

CustomFieldInput

Arguments

Name	Description
key <code>String!</code>	

Name	Description
value <code>String</code>	

DateRange

Arguments

Name	Description
start <code>Date</code>	
end <code>Date</code>	

DateTimeRange

Arguments

Name	Description
start <code>DateTime</code>	
end <code>DateTime</code>	

DonationDomain

Arguments

Name	Description
filters <code>DonationFiltersInput</code>	
ids <code>[Int!]</code>	

DonationFiltersInput

Arguments

Name	Description
------	-------------

q String	
archived Boolean	
order String	
tags [String!]	
tagsNot [String!]	
createDate DateRange	
createDatetime DateTimeRange	
updateDate DateRange	
updateDatetime DateRange	
completedDate DateRange	
completedDatetime DateTimeRange	
totalPaid IntRange	
totalPayments IntRange	
supporterType SupporterType	
campaigns [Int!]	
peerCampaigns [Int!]	
supporters [Int!]	
paymentMethods [Int!]	
frequencies [Frequency!]	
customfields [CustomFieldEntityFilter!]	

DonationInput

Arguments

Name	Description
amount Float	
frequency Frequency	
note String	
tags [String!]	
device String	
isPublic Boolean	
customfields [CustomFieldInput!]	

DonationPaymentInput

Arguments

Name	Description
amount Float	
frequency Frequency	
paymentDate DateTime	
paymentMethodId Int	

IntRange

Arguments

Name	Description
start Int	
end Int	

ManualPaymentInput

Arguments

Name	Description
amount Float!	
paymentDate DateTime!	
paymentMethodId Int	

ManualPaymentMethodInput

Arguments

Name	Description
label String!	
hasOneoffSupport Boolean	
hasSubscriptionSupport Boolean	
description String	
instructions String	
channels [Int!]	
includeInCertificate Boolean	

MenuInput

Arguments

Name	Description
name String!	
handle String!	

Name	Description
items [MenuItemInput!!]	

MenuItemInput

Arguments

Name	Description
label [String!]	
link [String]	

OrganizationInput

Arguments

Name	Description
name [String!]	
logo [Int]	
legalName [String]	
currency [Currencies!]	
isInvoiceRequired [Boolean]	
vat [String]	
vatExchange [String]	
taxIdentificationNumber [String]	
senderEmail [String]	
contactEmail [String]	
contactPhone [String]	

Name	Description
addressLine1 <code>String</code>	
addressLine2 <code>String</code>	
city <code>String</code>	
state <code>String</code>	
country <code>String</code>	
postalCode <code>String</code>	
annualCertificateAutoSend <code>Boolean</code>	
annualCertificateSendMonth <code>Int</code>	
annualCertificateSendDay <code>Int</code>	

OrganizationLegalInput

Arguments

Name	Description
tos <code>String!</code>	
privacyPolicy <code>String!</code>	
consentScopes <code>[String!]!</code>	

OrganizationsFilters

Arguments

Name	Description
name <code>String</code>	

PageInput

Arguments

Name	Description
title <code>String</code>	
content <code>String</code>	
visibility <code>WebDocumentVisibility</code>	
slug <code>String</code>	
seoTitle <code>String</code>	
seoDescription <code>String</code>	
template <code>String</code>	
coverId <code>Int</code>	

PagesFiltersInput

Arguments

Name	Description
q <code>String</code>	

PaginationInput

Arguments

Name	Description
first <code>Int</code>	
last <code>Int</code>	
after <code>String</code>	

Name	Description
before <code>String</code>	

PaymentDomain

Arguments

Name	Description
filters <code>PaymentFiltersInput</code>	
ids <code>[Int!]</code>	

PaymentFiltersInput

Arguments

Name	Description
q <code>String</code>	
supporter <code>Int</code>	
donation <code>Int</code>	
paymentMethod <code>Int</code>	
paymentDate <code>DateRange</code>	
state <code>[PaymentState!]</code>	
order <code>String</code>	
createDate <code>DateRange</code>	
updateDate <code>DateRange</code>	

PeerCampaignFilters

Arguments

Name	Description
q <code>String</code>	
ids <code>[Int!]</code>	
order <code>String</code>	
tags <code>[String!]</code>	
tagsNot <code>[String!]</code>	
channels <code>[String!]</code>	
supporterId <code>Int</code>	
campaignId <code>Int</code>	

PeerCampaignInput

Arguments

Name	Description
supporterId <code>Int!</code>	
campaignId <code>Int!</code>	
title <code>String</code>	
content <code>String</code>	
visibility <code>WebDocumentVisibility</code>	
slug <code>String</code>	
seoTitle <code>String</code>	
seoDescription <code>String</code>	
template <code>String</code>	

Name	Description
thankyouTemplate <code>String</code>	
coverId <code>Int</code>	
isGoalEnabled <code>Boolean</code>	
goal <code>Float</code>	
supporterName <code>String</code>	
customMessage <code>String</code>	
receiptNotificationId <code>Int</code>	

PrivacyDefinitionCreateInput

Arguments

Name	Description
code <code>String!</code>	
label <code>String!</code>	
message <code>String</code>	
isDefault <code>Boolean</code>	
isRequired <code>Boolean</code>	
consentScopes <code>[String!]</code>	

PrivacyDefinitionFilters

Arguments

Name	Description
code <code>String</code>	

Name	Description
label <code>String</code>	
isDefault <code>Boolean</code>	
isRequired <code>Boolean</code>	

PrivacyDefinitionUpdateInput

Arguments

Name	Description
code <code>String</code>	
label <code>String</code>	
message <code>String</code>	
isDefault <code>Boolean</code>	
isRequired <code>Boolean</code>	
consentScopes <code>[String!]</code>	

ProjectFilters

Arguments

Name	Description
q <code>String</code>	
order <code>String</code>	

ProjectInput

Arguments

Name	Description
title <code>String!</code>	
content <code>String</code>	
visibility <code>WebDocumentVisibility</code>	
slug <code>String</code>	
seoTitle <code>String</code>	
seoDescription <code>String</code>	
template <code>String</code>	
coverId <code>Int</code>	
type <code>ProjectType</code>	
rulesMatch <code>ProjectRuleMatchType</code>	
campaignsOrder <code>ProjectCampaignsOrder</code>	
rules <code>[ProjectRuleInput!]</code>	

ProjectRuleInput

Arguments

Name	Description
field <code>ProjectRuleField!</code>	
operator <code>ProjectRuleOperator!</code>	
value <code>String!</code>	
uuid <code>String!</code>	

RedirectInput

Arguments

Name	Description
sourcePath <code>String!</code>	
destinationUrl <code>String!</code>	

RedirectsFiltersInput

Arguments

Name	Description
q <code>String</code>	

SegmentFiltersInput

Arguments

Name	Description
entity <code>SegmentEntity!</code>	
q <code>String</code>	
order <code>String</code>	

SegmentInput

Arguments

Name	Description
name <code>String!</code>	
entity <code>SegmentEntity!</code>	
filters <code>String!</code>	

StripePaymentTypeInput

Arguments

Name	Description
types <code>[StripePaymentType!]!</code>	

SumUpAccountInput

Arguments

Name	Description
merchantCode <code>String</code>	

SupporterDomain

Arguments

Name	Description
filters <code>SupporterFiltersInput</code>	
ids <code>[Int!]</code>	

SupporterFiltersInput

Arguments

Name	Description
q <code>String</code>	
archived <code>Boolean</code>	
ids <code>[Int!]</code>	
order <code>String</code>	

Name	Description
type SupporterType	
city String	
country String	
createDate DateRange	
updateDate DateRange	
sex SexFilter	
campaigns [Int!]	
firstDonationDate DateRange	
lastDonationDate DateRange	
totalDonated IntRange	
totalDonations IntRange	
peerCampaigns [Int!]	
havePhone Boolean	
haveEmail Boolean	
haveVat Boolean	
haveSsn Boolean	
dateOfBirth DateRange	
placeOfBirth String	
emailMarketing Boolean	
phoneMarketing Boolean	
smsMarketing Boolean	

Name	Description
postalMarketing <code>Boolean</code>	
proflationMarketing <code>Boolean</code>	
privacyValues <code>[String!]</code>	
tags <code>[String!]</code>	
tagsNot <code>[String!]</code>	
isOneoffSupporter <code>Boolean</code>	
isRegularSupporter <code>Boolean</code>	
email <code>String</code>	
ssn <code>String</code>	
phone <code>String</code>	
customfields <code>[CustomFieldEntityFilter!]</code>	
query <code>String</code>	

SupporterInput

Arguments

Name	Description
businessName <code>String</code>	
firstName <code>String</code>	
lastName <code>String</code>	
title <code>String</code>	
externalRef <code>String</code>	

Name	Description
supporterType SupporterType	
email String	
phone String	
mobile String	
job String	
sex Sex	
dateOfBirth Date	
placeOfBirth String	
ssn String	
vat String	
address String	
address2 String	
city String	
locality String	
country String	
postalCode String	
emailMarketing Boolean	
phoneMarketing Boolean	
smsMarketing Boolean	
postalMarketing Boolean	
profilationMarketing Boolean	

Name	Description
note <code>String</code>	
certificationUrl <code>String</code>	
image <code>String</code>	
tags <code>[String!]</code>	
customfields <code>[CustomFieldInput!]</code>	
privacyValues <code>[SupporterPrivacyInput!]</code>	
sourceCampaignId <code>Int</code>	
sourcePeerCampaignId <code>Int</code>	

SupporterPrivacyInput

Arguments

Name	Description
code <code>String!</code>	
value <code>Boolean!</code>	
date <code>String</code>	

TerminalLocationFilters

Arguments

Name	Description
q <code>String</code>	

TerminalLocationInput

Arguments

Name	Description
displayName <code>String!</code>	
addressCity <code>String!</code>	
addressCountry <code>String!</code>	
addressLine1 <code>String!</code>	
addressLine2 <code>String</code>	
addressPostalCode <code>String!</code>	
addressState <code>String!</code>	

TerminalRegisterInput

Arguments

Name	Description
label <code>String!</code>	
registrationCode <code>String!</code>	
locationId <code>String!</code>	

Contenuto importato da <https://dev.riseact.org/docs/graphql-references/inputObjects> il 2026-04-23 durante la migrazione iniziale della KB Metadonors. Aggiornare se il sorgente cambia.

Revision #1

Created 2026-04-23 08:47:21 UTC by Daniele Cirio

Updated 2026-04-23 08:47:21 UTC by Daniele Cirio